

Power Wire Stripper

MAIN FEATURES

- Instant, accurate, effortless stripping of 8 to 30 AWG wire.
- Performs medium to high volume stripping with minimal investment.
- Utilizes pneumatic power with foot pedal actuation.
- Accepts die blades for Teflon and other difficult insulation

ACCESSORIES

- Foot Pedal **Cat. No. 45-902**
- Hook-up Kit **Cat No. 45-903**
- Air Blast Kit **Cat No. 45-905**
- Air Filter **Cat No. 45-906**



Knife Blades- For General Purpose Stripping
Hole Diameter (inches) for each AWG

Blade #	8	10	12	14	16	18	20	22	24	26	28	30
L-4419	0.159	0.141	0.106									
L-4420		0.144	0.105	0.085	0.073							
L-4421		0.144	0.113	0.09	0.072	0.061	0.048	0.048				
L-4422				0.09	0.072	0.061	0.039	0.039				
L-4452	For SP - SPT											
L-4994					0.072	0.061	0.048	0.039	0.032	0.026		
L-5361							0.048	0.039	0.032	0.026	0.021	0.016

TECHNICAL SPECIFICATIONS

WIRE SIZE

8-30 AWG (8mm²-0.05 mm²)

CUT LENGTH

Wire stop is adjustable to 0.625 in (15 mm).
Longer partial strips can be achieved by removing the wire stop

DIMENSIONS

Length: 3.625 in. (92 mm)
Width: 14.125 in. (359 mm)
Height: 4 in. (102 mm)

WEIGHT

6.5lbs (6.5 kg)

AIR REQUIREMENTS

60-100 psi (4-7 BAR)

Knife Blades- For General Purpose Stripping
Hole Diameter (mm) for each mm²

Blade #	10.00	6.00	4.00	2.50	1.50	1.00	0.50	0.22	0.20	0.13	0.08	0.05
L-4419	4.04	3.58	2.69									
L-4420		3.66	2.67	2.16	1.85	1.85						
L-4421		3.66	2.87	2.29	1.83	1.55	1.22	1.22				
L-4422				2.29	1.83	1.55	0.99	0.99				
L-4452	For SP - SPT											
L-4994					1.83	1.55	1.22	0.99	0.813	0.66		
L-5361							1.22	0.99	0.813	0.66	0.533	0.406