

The first name in wire processing

**ARTOS**  
ENGINEERING COMPANY

# CS-338

## PROGRAMMABLE WIRE PROCESSOR



### MAIN FEATURES



**Tractor feed belt system**  
(instead of rollers) for improved wire handling and less insulation damage.

**Measures, cuts and strips wire**  
from 30 AWG to 8 AWG (0,05 - 8mm<sup>2</sup>) wire dependent.



**Lever belt openers** facilitate quick, error-free wire change out.

# CS-338

**FASTER FEED RATES. MORE POWER.  
BETTER ERGONOMICS.**

**WE PROCESS  
THE WIDEST  
RANGE  
OF WIRE  
BAR NONE**



Simply put, the Artos CS-338 is one of the fastest, easiest-to-operate benchtop wire processors on the market today. This “next-generation” model features design improvements that give you maximum performance – and maximum value – for the investment.

With design modifications made over the previous CS-337 model, Artos engineers have achieved:

- a 75 percent faster feed rate
- a more ergonomically correct angled display for faster and easier programming
- improved cutting and stripping power to accommodate the widest possible range of wire

#### WIRE RANGE

30 AWG to 8 AWG (0,05 - 8mm<sup>2</sup>)  
wire dependent

#### MAX O.D.

.25" (6,35mm)

#### WIRE LENGTH

.06" (1,4mm) to 3937" (99,999mm)

#### STRIP LENGTH

.01" (.254mm) to 2" (50,8mm)

#### OUTPUT

Over 2,000 pcs/hr  
(rate is dependent on application)

#### ELECTRICAL REQUIREMENTS

110V or 240V

#### SIZE

16" x 12" x 10.5"  
(407mm x 305mm x 267mm)

#### WEIGHT

70 lbs. (31.75 kg)

*NOTE: Specifications are subject to change without notice*

## LOOK AT ALL THE CS-338 HAS TO OFFER

Ergonomic, angled operator display for fast, easy program entry of tasks:

- Inch or metric measurement
- Wire length calibration
- Automatic wire in-feed
- First piece trim feature
- Part program storage (up to 99 programs)
- Short wire mode-wire length less than 2" (51mm)

Convenient holders for guide storage – all necessary equipment stays with the machine

Lever belt openers allow quick, error-free wire change out

Quick adjust outfeed gap closure

All wire guides can be changed quickly without tools

Collection tray for stripping slugs – helps keep work area clean

Automatic wire pressure control

Feed belts for better wire handling

Wire run-out detection

