



UL Style 3173 Appliance Wiring

125°C - 600 volts AC - Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
Insulation: 125°C XLPE
RoHS and REACH Compliant

Compliances

CSA 1251
Voltage Rating 600 volts AC
Horizontal Flame per UL 1581
UL 758

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels, drums, returnable containers

Applications

Internal wiring of appliances

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
10	105	30	0.115	0.186	0.027	44	33
10	65	28	0.113	0.183	0.027	43	33
12	65	30	0.086	0.161	0.027	29	20
12	7	20	0.092	0.157	0.027	30	21
14	41	30	0.076	0.142	0.027	20	13
14	7	22	0.073	0.135	0.027	19	13
16	26	30	0.060	0.125	0.027	14	8
18	16	30	0.048	0.113	0.027	10	5
20	10	30	0.037	0.102	0.027	8	3
22	7	30	0.030	0.094	0.027	6	2

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com

