

UL Style 3199

Appliance Wiring

105°C - 300 volts AC - Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
 Insulation: 105°C XLPE
 RoHS and REACH Compliant

Compliances

CSA 1054
 Voltage Rating 300 volts AC
 Horizontal Flame per UL 1581
 UL 758

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors for base and stripe combinations
 Packaging options: reels, drums, returnable containers

Applications

In appliances or as ballast leads for indoor
 Use only.

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
18	19	30.5	0.045	0.082	0.013	7	5
16	26	30	0.060	0.096	0.013	11	8
20	10	30	0.038	0.075	0.013	5	3
22	7	30	0.030	0.065	0.013	4	2

Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com

