

# UL Style 3284

## Appliance Wiring

125°C - 600 volts AC- Horizontal Flame

### Features

Conductors available in solid or stranded, tinned or copper  
 Insulation: 125°C EPDM  
 RoHS and REACH Compliant

### Compliances

CSA CL-1254  
 Voltage Rating 600 volts AC  
 Horizontal Flame per UL 1581  
 UL 758

### Product Design Options

Custom strand constructions  
 Custom diameter to meet design criteria  
 Various colors for base and stripe combinations  
 Packaging options: reels, drums, returnable containers

### Applications

Internal Wiring of appliances

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
18	16	30	0.048	0.138	0.041	10	5
16	26	30	0.060	0.154	0.041	14	8
14	41	30	0.074	0.169	0.041	20	13
12	65	30	0.086	0.188	0.041	29	20
10	105	30	0.115	0.241	0.054	54	33
8	133	29	0.162	0.330	0.054	75	53
6	133	27	0.205	0.380	0.054	114	86
4	133	25	0.249	0.446	0.054	168	133
2	266	26	0.320	0.491	0.054	261	202
1	817	30	0.368	0.564	0.070	348	258
1/0	1045	30	0.399	0.610	0.070	423	323
2/0	1330	30	0.464	0.667	0.086	522	411
1/0	1672	30	0.515	0.714	0.070	642	516
4/0	2109	30	0.565	0.790	0.070	792	653

### Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.Prestolitewire.com](http://www.Prestolitewire.com)

Email: [bulkwiresales@prestolitewire.com](mailto:bulkwiresales@prestolitewire.com)

