

# UL Style 3374

## Appliance Wiring

125°C/150°C – 600 volts AC 750 volts DC- Horizontal Flame

### Features

Conductors available in solid or stranded, tinned or copper  
 Insulation: 125°C/150°C EPDM  
 RoHS and REACH Compliant

### Compliances

CSA AWM  
 Voltage Rating 600 volts AC 750 volts DC  
 Horizontal Flame per UL 1581  
 UL 758

### Product Design Options

Custom strand constructions  
 Custom diameter to meet design criteria  
 Various colors for base and stripe combinations  
 Packaging options: reels, drums, returnable containers

### Applications

Internal Wiring of appliances

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
20	10	30	0.038	0.143	0.040	12	3
18	16	30	0.048	0.166	0.040	16	5
16	26	30	0.060	0.166	0.041	19	8
14	41	30	0.074	0.180	0.041	25	13
12	65	30	0.086	0.188	0.041	33	20
10	65	28	0.113	0.226	0.040	50	33
8	133	29	0.162	0.338	0.054	93	53
6	133	27	0.205	0.357	0.054	125	86
4	133	25	0.249	0.435	0.054	191	133
3	525	30	0.256	0.459	0.054	230	163
2	266	26	0.320	0.522	0.054	280	202
1	817	30	0.368	0.570	0.072	346	258
1/0	1045	30	0.399	0.608	0.072	428	323
2/0	1333	30	0.464	0.707	0.072	542	411
3/0	1672	30	0.515	0.765	0.072	664	516
4/0	2109	30	0.565	0.780	0.072	796	653

### Customer Service Group

1 Prestolite Drive

Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.Prestolitewire.com](http://www.Prestolitewire.com)

Email: [bulkwiresales@prestolitewire.com](mailto:bulkwiresales@prestolitewire.com)

